

AL02-03-100 : Semi Automatic Benchtop Autoclave

Suitable for the sterilization of:

- Liquids such as nutrient media and buffer solutions
- Solid items such as pipettes, tubes and filters
- Glassware and plastic articles
- Waste sterilization



Features:

- **Heat-resistant plastic covering on lid** Prevents contact with hot parts and protects from burning.
- **Pressure-dependent door lock** Prevents the door from being opened when under pressure.
- **Door lock safety switch** Prevents the sterilization program from being started if the door has not been closed properly.
- **Excess temperature safety device** Switches off the heating elements if too high a temperature is attained.
- **Overpressure valve** Releases over pressure in order to prevent high pressure risk.

Technical Specification:

Chamber Volume (liter):	23
Chamber Size (øxDiameter in mm):	250x420
Voltage(nominal +/-10%) 50/60Hz (V):	220-240
Heating Capacity (Kw):	2.2
Ambient Temperature (°C):	5 to 40 degrees
Control:	Semi Automatic
Dimensions* WidthxHeightxDiameter (mm):	510x365x545
Shipping Weight :	48 kg

*Dimensions refer to unit housing including levelling feet. Technical data are subject to change without prior notice.

Loading Capacity:

Erlenmeyer	Nr. of bottles	Schott-Duran	Nr. of Bottles
250 mL	10	250 mL	14
500 mL	8	500 mL	10
1000 mL	3	1000 mL	4
2000 mL	-	2000 mL	-
3000 mL	-	5000 mL	-
5000 mL	-	10000 mL	-