

AL02-02-100 : Fully Automatic Vertical Autoclave



Suitable for the sterilization of:

- Liquids such as nutrient media and buffer solutions
- Solid items such as pipettes, tubes and filters
- Glassware and plastic articles
- Waste sterilization

Features:

- **Pressure-dependent door lock** prevents door opening when under pressure.
- **Programs** - 6 individual programs standard available
- **Sterilization Parameters** - Temperature and time are freely selectable;
- Temperature can be set between 60 and 137°C. Sterilization time can be set from 1–99 minutes. Pre-selected parameters remain programmed until altered.
- **Temperature-dependent door lock** - In conjunction with temperature control in a reference bottle, the system prevents the door from being opened until the temperature is below a specified level, thereby preventing delayed boiling (as specified by technical safety regulations, in compliance with European and International standards).
- **Water level safety device** - Prevents the autoclave from being heated up if insufficient water is available for steam generation.

Technical Specification:

Chamber Volume (liter):	23
Chamber Size (øxDiameter in mm):	250x400
Voltage(nominal +/-10%) 50/60Hz (V):	220-240
Heating Capacity (Kw):	2.2
Ambient Temperature (°C):	5 to 40 degrees
Control:	Fully Automatic
Displays:	Temperature, Pressure and Time
Alarm:	Visible and Acoustic
Dimensions* WidthxHeightxDiameter (mm):	500x665x335
Shipping Weight :	57 kg

*Dimensions refer to unit housing including levelling feet. Technical data are subject to change without prior notice.

Loading Capacity:

Erlenmeyer	Nr. of bottles	Schott-Duran	Nr. of Bottles
250 mL	2 x 5	250 mL	2 x 8
500 mL	2 x 4	500 mL	2 x 5
1000 mL	1	1000 mL	4
2000 mL	1	2000 mL	1
3000 mL	1	5000 mL	1
5000 mL	1	10000 mL	-