## A02-11-100 : Semi Automatic Benchtop Autoclave

Suitable for the sterilization of:

- Liquids such as nutrient media and buffer solutions
- Solid items such as pipettes, tubes and filters
- Glassware and plastic articles
- Waste sterilization

## Features:

- Heat-resistant plastic covering on lid Prevents contact with hot parts and protects from burning.
- **Pressure-dependent door lock** Prevents the door from being opened when under pressure.
- **Door lock safety switch** Prevents the sterilization program from being started if the door has not been closed properly.
- Excess temperature safety device Switches off the heating elements if too high a temperature is attained.
- Overpressure valve Releases over pressure in order to prevent high pressure risk.

## **Technical Specification:**

Chamber Volume (liter): 62

 Chamber Size (øxDepth in mm):
 380x510

 Voltage(nominal +/-10%) 50/60Hz (V):
 230 / 1Ph

Heating Capacity (Kw): 4.0

Ambient Temperature (℃):5 to 40 degreesControl:Semi AutomaticDimensions\* WidthxHeightxDepth (mm):660x525x695

Shipping Weight: 80 kg

## **Loading Capacity:**

Erlenmeyer	Nr. of bottles	Schott-Duran	Nr. of Bottles
250 mL	22	250 mL	28
500 mL	15	500 mL	20
1000 mL	8	1000 mL	15
2000 mL	5	2000 mL	8
3000 mL	3	5000 mL	3
5000 mL	-	10000 mL	-



<sup>\*</sup>Dimensions refer to unit housing including levelling feet. Technical data are subject to change without prior notice.