

pipet4u® OASIS

Pipette Controller

Features



Secure handling
Replacable membrane filter to minimize risk of contamination

Pipetting speed control
Adapt pipetting speed depending on sample viscosity with 3 selectable speeds

- Comfortable and effortless pipetting**
Light weight pipette design
Smooth push buttons for precise pipetting control
Ergonomic design for easy operation
Cordless working (8 hours with no need to recharge)
Silent high power motor

pipet4u® OASIS

Pipette Controller

Specifications | Order Information

Volume Range	Description	Sales Unit	Cat. No.
0.1 - 100 ml	pipet4u® OASIS Pipette Controller	Carton/1 OASIS	8-300-00-9

- Included Accessories**
- 2 x NiMH batteries
 - Desktop stand
 - Wall mount bracket
 - Charger
 - 2 x PTFE membrane filter
 - Instruction manual

Spare Parts pipet4u® OASIS Pipette Controller

Pore Size	Description	Sales Unit	Cat. No.
0.20 µm	pipet4u® OASIS PTFE membrane filters	Carton/5 filters	8-300-03-0
0.45 µm	pipet4u® OASIS PTFE membrane filters	Carton/5 filters	8-300-04-0
	pipet4u® OASIS silicone adapter	Carton/1 adapter	8-300-01-0
	pipet4u® OASIS pipette cone	Carton/1 cone	8-300-02-0

Pipette Controller Specifications | Order Information

Information comes at time of printing.



Pipette Controller Features

Information comes at time of printing.