



# MiniRAE 3000

## Portable Handheld VOC Monitor

MR02 / 20100201

The MiniRAE 3000 is the most advanced handheld volatile organic compound (VOC) monitor on the market. Its photoionization detector's (PID) extended range of **0 to 15,000 ppm** makes it an ideal instrument for applications from industrial hygiene to leak detection and HazMat.

The **RF modem allows real-time data transmissions** with a base controller located up to 500 feet away from the MiniRAE 3000 (or two miles with optional RAELink3 portable modem). A personal computer can be used as the base station for a MiniRAE 3000 system. The standard ProRAE Remote software is capable of monitoring the input of up to 64 remotely located monitors, including MiniRAE 3000, AreaRAE, etc.



### Key Features

- **Proven PID technology**  
The patented sensor provides the following unique features:
  - 3-second response time
  - Extended range up to 15,000 ppm with improved linearity
  - Humidity compensation with integral humidity and temperature sensors
- **Real-time wireless** data transmission with built-in RF modem or Bluetooth
- **Designed for simple service** Easy access to lamp and sensor in seconds without tools
- **Big graphic display** for easy overview of gas type, Correction Factor and concentration
- **Field-interchangeable battery pack** replaced in seconds without tools
- **Integrated flashlight** for better view in dark conditions
- **User-friendly screens, including dataplot chart view**
- **Integrated RAE Systems Correction Factors list for more than 200 compounds** to measure more chemicals than any other PID
- **Multi-language support** with 12 languages encoded
- **Rugged housing** withstands use in harsh environments
  - IP67 waterproof design for easy cleaning and decontamination in water
  - Strong protective removable rubber boot

### Additional Advantages

- View real-time sensor data and alarm status at headquarters or command center
- Automatic lamp type recognition
- Duty-cycling™ lamp and sensor auto-cleaning technology
- Tough, flexible inlet Flexi-Probe™
- 3 large keys operable with 3 layers of gloves
- Strong, built-in sample pump draws up to 100 feet (30m) horizontally or vertically
- Loud, 95dB audible alarm
- Bright red flashing visual alarm
- Interchangeable drop-in lithium-ion and alkaline battery packs
- Charging cradle doubles as an external battery charger
- Compatible with AutoRAE™ calibration station
- ProRAE Remote software simultaneously controls and displays readings for up to 64 remote detectors
- License-free, ISM band RF transmission with communication range up to 500 feet (2 miles with optional RAELink3 modem)
- Optional RAELink3 modem provides GPS capability to track and display readings from remote detectors and provide up to 2 miles' long-distance transmission
- Datalogging with up to 6 months of data at one-minute intervals
- 3-year 10.6eV lamp warranty



ver1\_06.07

[www.raesystems.com](http://www.raesystems.com)



ATEX



IECEX



Waterra

# MiniRAE 3000

## Specifications\*

### Detector Specifications

<b>Size</b>	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
<b>Weight</b>	26 oz (738 g)
<b>Sensors</b>	Photoionization sensor with standard 10.6 eV or optional 9.8 eV or 11.7 eV lamps
<b>Battery</b>	<ul style="list-style-type: none"><li>• Rechargeable, external field-replaceable Lithium-Ion battery pack</li><li>• Alkaline battery adapter</li></ul>
<b>Operating Hours</b>	16 hours of operation (12 hours with alkaline battery)
<b>Display Graphic</b>	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
<b>Keypad</b>	1 operation and 2 programming keys, 1 flashlight on/off
<b>Direct Readout</b>	Instantaneous reading <ul style="list-style-type: none"><li>• VOCs as ppm by volume</li><li>• High values</li><li>• STEL and TWA</li><li>• Battery and shutdown voltage</li><li>• Date, time, temperature</li></ul>
<b>Alarms</b>	95 dB (at 30 cm) buzzer and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none"><li>• High: 3 beeps and flashes per second</li><li>• Low: 2 beeps and flashes per second</li><li>• STEL and TWA: 1 beep and flash per second</li><li>• Alarms latching with manual override or automatic reset</li><li>• Additional diagnostic alarm and display message for low battery and pump stall</li></ul>
<b>EMI/RFI</b>	Highly resistant to EMI/RFI Compliant with EMC Directive 89/336/EEC
<b>IP Rating</b>	<ul style="list-style-type: none"><li>• IP67 unit off and without flexible probe</li><li>• IP65 unit running</li></ul>
<b>Datalogging</b>	Standard 6 months at one-minute intervals
<b>Calibration</b>	Two-point or three-point calibration for zero and span. Calibration memory for 8 calibration gases, alarm limits, span values and calibration dates
<b>Sampling Pump</b>	<ul style="list-style-type: none"><li>• Internal, integrated flow rate at 500 cc/mn</li><li>• Sample from 100' (30m) horizontally and vertically</li></ul>
<b>Low Flow Alarm</b>	<ul style="list-style-type: none"><li>• Auto pump shutoff at low-flow condition</li></ul>
<b>Communication</b>	<ul style="list-style-type: none"><li>• Download data and upload instrument set-up from PC through charging cradle or optional Bluetooth™</li><li>• Wireless data transmission through built-in RF modem</li></ul>
<b>Frequency</b>	902 to 928 MHz (license-free), 2.400 to 2.4835 GHz (license-free), 433 MHz, 869 MHz
<b>RF Range</b>	Up to 500' (900 MHz, 433 Mhz, 869 Mhz), extendable with RAELink3 Repeater to 2 miles
<b>Hazard Area Approval</b>	<ul style="list-style-type: none"><li>• <b>US and Canada:</b> UL, cUL, Classified as Intrinsically Safe for use in Class I, Division I Groups A, B, C, D</li><li>• <b>Europe:</b> ATEX II 1G EEx ia IIC T4 (pending)</li><li>• <b>IECEX:</b> II 1G EEx ia IIC T4 (pending)</li></ul>
<b>Temperature</b>	-4° to 113° F (-20° to 50° C)
<b>Humidity</b>	0% to 95% relative humidity (non-condensing)
<b>Attachments</b>	Durable bright yellow rubber boot with belt clip
<b>Warranty</b>	Lifetime on non-consumable components (per RAE Systems Standard Warranty), 3-year warranty for 10.6 eV lamp, 1 year for pump and battery

\*Specifications are subject to change

### Sensor Specifications

Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 999.9 ppm	0.1 ppm	< 3 s
	1000 to 15,000 ppm	1 ppm	< 3 s

### Monitor only includes:

- MiniRAE 3000 Monitor, Model PGM-7320
- Wireless communication module built in, as specified
- Datalogging with ProRAE Studio Package for Windows™ 95, 98, 2000, NT, ME & XP
- Charging/download adapter
- RAE UV lamp, as specified
- Flex-I-Probe™
- External filter
- Rubber boot
- Alkaline battery adapter
- Lamp-cleaning kit
- Tool kit
- Operation CD-ROM
- Operation & Maintenance manual
- Soft leather case

### Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- Charging/download cradle
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

### Optional calibration kit adds:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

DISTRIBUTED BY: **Waterra**

ver1\_06.07

**Waterra UK Limited**  
**Tel: +44 (0) 121 733 7743 / 7745**  
**[sales@waterrauk.com](mailto:sales@waterrauk.com) / [www.waterrauk.com](http://www.waterrauk.com)**

**[www.raesystems.com](http://www.raesystems.com)**

