



UT-2600C

**Features:**

- Fully automatic.
- Easy Windows operation system, large LCD display.
- Washes flat, U and V-bottom strips and plates.
- 12-way or 8-way manifold, automatic and manual positioning.
- Large memory, up to 50 wash protocols can be programmed.
- Automatic monitoring for vacuum and pressure, automatic rinse cycle.
- Washing pressure volume and time adjustable.
- Liquid level detection & alert function
- No special airtight bottle required for wash bottle.
- Easy maintenance.

**UT-2600C, Microplate Washer**

Model	UT-2600C
Plate Mode	96-/48-well plate or strip
Dispense Precision	CV<2.0%
Residual Volume	<1 $\mu$ l
Washing Volume	50~3000 $\mu$ L for 8-way manifold 50~2000 $\mu$ L for 12-way manifold
Washing Cycle	Maximum 99 cycles
Strip Washing	1 to 12 strips programmable
Soaking Time	0~24hours
Shaking Time	0~24hours
Display	5" LCD
Wash Channels	3 channel bottles, 1 for wash, 1 for water(rinse) and 1 for waste
Bottles Capacity	2 Liters each bottle
Memory	50 washing protocols
Interface	RS-232
Power Supply	AC 110/220V $\pm$ 10%, 50~60HZ
Net Weight	8KG
Dimension (mm)	L390xW340xH180



UT-3100-5

**Features:**

- Fully automatic.
- User friendly operation system with large LCD display.
- Washes flat, U and V-bottom strips and plate.
- 12-way or 8-way manifold, automatic and manual positioning.
- Large memory, up to 100 wash protocols can be programmed.
- Multi-channel, 1 or 3 (optional) for wash, 1 for rinse and 1 for waste.
- Plate shaking function, time and speed are adjustable.
- Two 96-well plate incubation positions (optional)
- Liquid level detection & alert function.
- Easy maintenance.

**UT-3100-5, Microplate Washer, 5 Channels, Build-In Incubator**

Model	UT-3100-5
Plate Mode	96-/48-well plate or strip
Residual Volume	<1 $\mu$ l
Washing Volume	10~3000 $\mu$ l/well, 1 $\mu$ l by step
Washing Cycle	Maximum 99 cycles
Strip Washing	1 to 12 strips programmable
Soaking Time	0~24hours
Shaking Time	0~24hours
Display	Large LCD
Wash Channels	5 channel bottles, 1 or 3 (optional) for wash, 1 for water(rinse) and 1 for waste
Bottles Capacity	2 Liters each bottle
Memory	100 washing protocols
Interface	RS-232
Power Supply	AC 110/220V $\pm$ 10%, 50~60HZ
Net Weight	13 KG
Dimension (mm)	L450xW390xH190