

A 10-second Magic

All new spin-down function in Centrifuge made by Hanil. It is light, small and decreasing test time innovatively.

Micro 6

6,500 MAX. RPM	2,234 MAX. RCF	1.5/2.0ml X 6 MAX. CAP
--------------------------	--------------------------	----------------------------------



Features

- Co-using Angle & PCR rotor
- Spin down/continuous switching
- BLDC Motor-Brushless motor provides maintenance free operation
- BLDC motor for faster acceleration and deceleration
- Electro sensitive non-contacting door sensor
- Avoidance of contamination by carbon powder from motor



A1.5/2.0M-6



A0.2M-16



- Operating when door closing
- Spin down mode - app. 15 sec.
- Continuous mode - app. 15 min.



2 action mode

Automatically operating from door shutting, options for basic(15sec) and continuous.



2 type rotor

Including Micro rotor and Strip rotor (0.5/1.5/2.0 ml x 6 , adapter 0.5ml x 6) Great rotor compatibility.

Description	Specification	Remarks
RPM / RCF	6,500 / 2,234 xg	A1.5/2.0ml x 6 A0.2ml x 16
Max. capacity	1.5/2.0ml x 6	
Motor	BLDC / 30W	
Accel/Decel	Accel 9 sec. / Decel 6 sec.	6,500rpm
Rotor	1.5/2.0ml x 6 PCR 0.2ml x 16hole	
Power supply	110/220V, 50/60Hz	
Dimension	150W x 160D x 94H/mm	
Weight, g	750g	

* Please note that technical specifications subject to change.