




Multipurpose Centrifuge

Multipurpose Refrigerated centrifuge

Multipurpose refrigerating floor type centrifuge generally used for labs in hospitals and universities on reasonable price level.

Union 55R

Swingout rotor

TEMP -10 °C to +40 °C	5,500 MAX. RPM	5,411 MAX. RCF	15ml X 32 MAX. CAP	
				



Features

- One chip Microprocessor control
- Easy-to-use control
- Environmentally refrigerating system of cfc-free and efficient cooling
- RPM/RCF auto calculating
- Feedback control system
- Brushless AC Induction motor
- Memory for saving experiment condition
- Temperature control system for delicate experiment

Powerful AC Motors & Cooling System

Environmentally refrigerating system of cfc-free and efficient cooling.

Easily moveable type of floor standing

Tubes of various volumes



Description	Specification	Remarks
RPM	5,500rpm	
RCF	5,411 xg	
Max. capacity	15ml x 32	
Time	9hrs 59min 59sec	
Display	RPM, RCF, Time,Temp, Program, Accel/Decel Rotor Number, Rotor Radius	
Warning display	Imbalance, Door open, Over speed, Over temp	
Temp	-10 °C ~ 40 °C	
Accel/Decel	3 step	
Motor	AC Induction Motor	
Power supply	110V/220V, 60Hz, single phase	
Dimension	570W x 475D x 325H/mm	
Weight, Kg	122Kg	

* Please note that technical specifications subject to change.